

## PRODUCT INFORMATION DATA SHEET

# LIB DISPERSANT - 1010

- DESCRIPTION** : Copolymer with Oleochemical Derivative
- SPECIFICATIONS** :
- Appearance : Free flow off White Powder
  - Melting Point : 103 - 108°C
  - Flash Point : > 280°C
- PROPERTIES** :
- Remarkable disperse ability for general purpose colour and black Masterbatches/Compounds.
  - Reduce the FPV (Filter Pressure Value) in any kind of Thermoplastic's masterbatches.
  - Improve the Production Rate and Melt Viscosity while processing.
  - Available at Excellent CPR (cost and performance ratio).
- APPLICATIONS** :
- General purpose masterbatches like Films, Moldings, Pipes, Wovensacks, Monolayer films etc.
  - Wax based and single pigment Masterbatches or MOC (Mono Organic Compounds)
  - General Thermoplastics Compounds Like automotive, electrical, home appliances etc.
- DOSAGE** :
- Special application MBs : 20 to 25 Phr.
  - General Purpose MBs : 04 to 10 Phr.
  - Other masterbatches/compounds : 2.5 to 5.0 Phr.
- SALIENT FEATURE** :
- Compatible for PE, PP, PS, Group Polymers.
  - Recommended for Pretreatment of Fine Minerals and Pigments.
  - Easy in blending or mixing due to its free flow property.
  - Remarkable results in improvements of Die Lip Problem.