

PRODUCT INFORMATION DATA SHEET

LIBNOL G-9 I

DESCRIPTION	:	Oleaochemical Derivative
SPECIFICATIONS	:	Appearance : Clear Liquid Moisture : 0.1 Max
PROPERTIES	:	<ul style="list-style-type: none">• Internal Lubricant with release properties• Suitable for use in transparent Products• Easy processability• Improves gloss and surface finish• Secondary plasticizing efficiency
APPLICATIONS	:	<p><i>Recommended for Rigid/Plasticized PVC applications</i></p> <ul style="list-style-type: none">• Transparent rigid/plasticized PVC blown films• Plasticized PVC injection moulded articles like footwear• Suggested for use in rigid/soft PVC profiles / hoses <p><i>Polyolefins / EVA compounds & Masterbatches</i></p> <ul style="list-style-type: none">• Excellent dispersing properties of Libnol G-9I enable uniform dispersion of fillers• Suitable wetting and dispersing agent for filled polyolefins/ EVA compounds & masterbatches• Efficiently replaces conventional products like paraffin oils, LNP and others
DOSAGE	:	0.5 - 1.5% phr in PVC applications 0.5 - 1.0 % as wetting & dispersing in polyolefins / EVA compound
STABILIZATION	:	Suitable for use with all commercially available stabilizers